

SMD High Current Inductor
Size 2015

- I лЭK äI-údzNI-ə2y'ÖdzNIUSyú dzLJ ú2 млл !
- [2Ø t2ääŠă ØłúK bI-ú ØłUS ŘŠăłЭY
- [2Ø Ö2US t2ääŠă ØłúK a yÎy'Ö2US YI-úŠNIłI-f
- vdzI-yəúëY мллLJÖă
- I лЭK ÖdzNIUSyú 5 / κ5 / Ö2yØŠNIúŠNI
- [/ ŮtúŠNI

Dimensions: [mm]

Land Pattern: [mm]



Electrical Properties:

hLJŠNI-əyЭ ¢SYLJŠNI-údzNISY ππл °C ú2 Ъмнр °C
¢SYLJŠNI-údzNIS wIăŠ / dzNIUSyúŮ úKŠ I-ÖúdzI-f ØI-fdzŠ 2T 5 / ÖdzNIUSyú ØKŠy'úKŠ úSYLJŠNI-údzNIS NIăŠ Iă p¢πл °C
{I-údzNI-ə2y' / dzNIUSyú úKI-ú Øłft ŐI-dzăŠ IyIəI-f IyŘdzŐúI-yŐŠ ú2 ŘNI2LJ I-LJLNI2ËIYI-úŠfê HđĤ:

Typical Electrical Characteristics:

